



TECHNICAL DATA SHEET

PRODUCT: SAVON DE MARSEILLE

DESCRIPTION

SAVON DE MARSEILLE is a special ecological water-based dirt protective, for all glossy lime-based mineral finishing:

- glossy plaster in all its range;
- Venetian plaster in all its range.

SAVON DE MARSEILLE is composed by genuine *savon de Marseille* and additives in a homogeneous blend.

SAVON DE MARSEILLE confers to the surface a regular *washability*, without altering its breathable properties.

SAVON DE MARSEILLE is VOC free and suitable for **indoor** wall surfaces protection.

APPLICATION

Let the surface dry out for at least **48 hours**, then spread a coat of **savon de marseille** with the *Inox* trowel.

Apply more times **wet on wet** until the surface has completely absorbed, then **remove** the excess of soap from the surface by using the trowel with the steel blade sloping at 90°.

Wait further **48 hours** and rub the surface with a cloth to remove the soap dust.

STORAGE

The product maintains its properties for a period of 24 months if protected from excessive heat and cold. The storage temperature must be included between **+5°C** and **+30°C**. Protect from frost.

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For more information consult the safety sheet.

DISPOSAL

The product must be disposed in agreement with current regulations. Empty containers have to be sent to recycling plants.

TECHNICAL SPECIFICATIONS

Appearance	thick paste, ready to use
Colour	transparent neutral white
Packaging	2Kg net
Application tools	<i>Inox</i> steel finishing trowel
Specific weight	0,66 ± 0,02Kg/l
pH	7,5 ± 1
Nominal yield	30 ÷ 60g/m ²
Environmental temperature	min +5°C, max +30°C
Dry to the touch	2 hours with environmental temperature of 20°C
Dry to handle	48 hours with environmental temperature of 20°C
VOC classification As per Dir. 2004/42/EC, Cat. A/I: Decorative effect coatings EU limit value: 300g/l (2007), 200g/l (2010)	0 g/l of VOC if uncoloured

The information contained in this sheet has only informative value, as we cannot consider the specific conditions of each application.

Issued by:	Export Manager or External Institution	Approved by:	Export Manager	
	COVERIT s.r.l. Strada Marchesane 123; 36061 Bassano del Grappa (VI) Tel. +39.0424.500.507 – Fax. +39.0424.500.110 e-mail: info@coverit.it – web: www.coverit.it	Document	ST019ING	
		Issue date	24/10/05	
		Revision	02	
		Revision date	27/02/07	
Page 1 of 1				