



TECHNICAL DATA SHEET

PRODUCT: CERA NATURALE

DESCRIPTION

CERA NATURALE (Natural Wax) is a special water-based dirt protective, for all glossy lime-based mineral finishing:

- glossy plaster in all its range;
- Venetian plaster in all its range.

CERA NATURALE is composed by genuine bees wax, pure *savon de Marseille* and additives in an homogeneous blend. It's completely solvent free (0% VOC).

CERA NATURALE increases the glossiness and confers to the surface washable properties, maintaining an outstanding breathethrough capacity.

CERA NATURALE is suitable for **indoor** wall surfaces protection only.

APPLICATION

Ready to use, mix carefully before using.

Let the surface to dry out for at least **48 hours**.

Spread a coat of wax with a soft (non-abrasive) sponge for about 1m² only (about 11ft²), and continue the application until the wall doesn't absorb anymore.

Remove with paper cloth the excess of wax from the surface.

After about 30 minutes and before 2 hours, proceed to burnish with a non-woven fabric cloth (micro fibre or TNT/tissue-non-tissue cloth) or mechanic polisher.

STORAGE

The product maintains its properties for a period of 12 months if protected from excessive heat and cold. The storage temperature must be included between **+5°C** and **+30°C**. **Protect from frost.**

SAFETY GUIDELINES

Avoid contact with skin and eyes. If contact occurs, rinse thoroughly with water. For more information consult the safety sheet.

DISPOSAL

The product must be disposed in agreement with current regulations. Empty containers have to be sent to recycling plants.

TECHNICAL SPECIFICATIONS

Appearance	dense liquid
Colour	transparent neutral white
Packaging	2Kg
Application tools	non-woven fabric cloth or mechanical polisher
Specific weight	0,99 ± 0,05Kg/l
pH	11 ± 0,5
Nominal yield	30 ÷ 50g/m ²
Environmental temperature	min +10°C, max +30°C
Dry to the touch	1 hour with environmental temperature of 20°C
Dry to handle	48 hours with environmental temperature of 20°C
VOC classification As per Dir. 2004/42/EC, Cat. A/I: Decorative effect coatings EU limit value: 300g/l (2007), 200g/l (2010)	0 g/l of VOC if uncoloured

The information contained in this sheet has only informative value, as we cannot consider the specific conditions of each application.

Issued by:	Export Manager or External Institution	Approved by:	Export Manager	Document	ST020ING
	COVERIT s.r.l. Strada Marchesane 123; 36061 Bassano del Grappa (VI) Tel. +39.0424.500.507 – Fax. +39.0424.500.110 e-mail: info@coverit.it – web: www.coverit.it			Issue date	24/10/05
				Revision	05
				Revision date	27/02/07